

RAVELLI SRL

Via Kupfer, 31

25036 Palazzolo sull'Oglio (BS)

Tel. +39 030 7402939 Fax +39 030 7301758
info@ravelligroup.it + www.ravelligroup.it

DECLARATION OF PERFORMANCE

Declaration of performance according to Regulation (EU) 305/2011

n. 075CPR13.07

- Unique identification code of the product type: 033-00-001A, residential space heating appliance fired by wood pellets EN 14785:2006
- Type, batch or serial number or any other element allowing identification of the construction product as required under Art. 11 (4): NATURAL 11
- Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: Residential space heating appliance fired by wood pellets
- Name, registered trade name or registered trade mark and contact address of the manufacturer as required by Art. 11 (5): Ravelli s.r.l.

Via A. Kupfer, 31

25036 Palazzolo s/O (Bs) Italia

- 5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2):
- System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: System 3
- In case of the declaration of performance concerning a construction product covered by a harmonised standard:
 The notified laboratory TÜV Rheinland Energie und Umwelt GmbH (NB 2456) performed the determination of the product type on the basis of type testing under system 3 and issued test report K16802015T1

8. Declared performance

Harmonized technical specification:	EN 14785:2006			
Essential characteristics	Performance			
Fire safety				
Reaction to fire	A1			
Distance to combustible materials	Minimum distances (mm): rear = 100 sides = 150 front = 800 ceiling = 600 floor = —			
Risk of burning fuel falling out	Pass			
Emission of combustion products (at 13% of O_2)	Nominal heat output CO 0.008 % NOx 132.6 mg/Nm³ OGC 2.8 mg/Nm³ PM 18.7 mg/Nm³ Reduced heat output CO 0.028 % OGC 3.3 mg/Nm³			
Surface temperature	Pass			
Electrical safety	Pass			
Cleanability	Pass			
Maximum operating pressure	-			
Flue gas temperature at nominal heat output	197 °C			
Mechanical resistance(to carry a chimney/flue)	NPD			
Nominal heat output	9.8 kW			
Room heating output	9.8 kW			
Water heating output	-			
Efficiency	∏ 88.77 % Nominal heat output ∏ 94.84 % Reduced heat output			

9.	The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance
	is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for a	nd on behalf of the manufactur	ег	Stefano Ravelli, CEO	-	(name and title)
Place	Palazzolo s/O	Date	30-7-2015	Sign	fell fly