

RAVELLI SRL

Via Kupfer, 31 25036 Palazzolo sull'Oglio (BS)

Tel. +39 030 7402939 Fax +39 030 7301758 info@ravelligroup.it - www.ravelligroup.it

DECLARATION OF PERFORMANCE

Declaration of performance according to Regulation (EU) 305/2011

n. 031CPR13.07

- Unique identification code of the product type: 014-00-002A, residential space heating appliance fired by wood pellets EN 14785:2006
- Type, batch or serial number or any other element allowing identification of the construction product as required under Art. 11 (4): RC70
- Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer;
 Residential space heating appliance fired by wood pellets
- Name, registered trade name or registered trade mark and contact address of the manufacturer as required by Art. 11 (5): Ravelli s.r.l.

Via A. Kupfer, 31

25036 Palazzolo s/O (Bs) Italia

- Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2):
- System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: System 3
- In case of the declaration of performance concerning a construction product covered by a harmonised standard:
 The notified laboratory TÜV Rheinland Energie und Umwelt GmbH (NB 2456) performed the determination of the product type on the basis of type testing under system 3 and issued test report K12662014T1

8. Declared performance

Harmonized technical specification:	EN 14785:2006		
Essential characteristics	Performance		
Fire safety			
Reaction to fire	A1		
Distance to combustible materials	Minimum distances (mm): rear = 100 sides = 250 front = 800 ceiling = floor =		
Risk of burning fuel falling out	Pass		
Emission of combustion products (at 13% of O_2)	Nominal heat output CO 0,013 % NOx 140,9 mg/Nm³ OGC 2,8 mg/Nm³ PM 12 mg/Nm³ Reduced heat output CO 0,021 % OGC 1,5 mg/Nm³		
Surface temperature	Pass		
Electrical safety	Pass		
Cleanability	Pass		
Maximum operating pressure	N/A		
Flue gas temperature at nominal heat output	153 °C		
Mechanical resistance (to carry a chimney/flue)	NPD		
Nominal heat output	7,4 kW		
Room heating output	7,4 kW		
Water heating output	N/A		
Efficiency	Π 90,3 % Nominal heat output Π 92,5 % Reduced heat output		

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance
is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for an	d on behalf of the manufacture	er	Stefano Ravelli, CEO	(name and title)
Place	_ Palazzolo s/O	Date	21/8/2014	Sign/_